Smartsign[®]

Qbic BXP-300/301 with Smartsign.



Focus on smooth 4K content.

Save time and avoid trouble.

Focus more on your content and less on installation and technical hassle. The Qbic player always comes with the latest version of Smartsign preinstalled. All you need to do is choose if you want a local installation or use our cloud service.

Ultra Smooth 4K Resolution*

A powerful video processor handles intensive high frame rate video for smooth playback, easily connected to your 4K screens. BXP-301 also supports 1080p HDMI in for PiP.

A box with the little extra.

The Qbic player also supports remote access support through Teamviewer and also for maintenance purposes for IT departments. The player also supports touch screens and has built-in memory protection if something goes wrong. All in a rugged shell that can handle tough environments.

*4k UHD Video playback, other content is displayed in 1920*1080



Book a personal demo

Send us an email and your number to **info@smartsign.se** and we will contact you. We'll review step by step how to use our smart solutions for your specific needs. When you book a demo, we will contact you and match your needs and then book an online demo. We often do this on the same day over the internet. Player BXP 300/BXP301 from Qbic Technology

Product numbers: SDM-QBIC-BXP300-S SDM-QBIC-BXP301-S



+46 10 410 77 00 / info@smartsign.se / smartsignmanager.com

Smartsign was founded in Sweden in 1998 and is now one of the world's leading digital signage software for publishing and managing internal and external communications. Today Smartsign has offices in parts of Europe, the Middle East and Australia. Smartsign's software is on displays in over 30 countries and has become the most sought after digital signage software across the industry.

Ultra Smooth 4K Resolution



BXP-300/BXP-301

Features

Video Playback Engine	H.265 4K@60p, H.264 4K@30p
Video Resolution	4K UHD 3840*2160 @60fps
Content resolution	1920*1080
HDMI CEC	Yes
Operating System	Android 5.1
Orientation display	
CPU	ARM Quad-core 1.8GHz
GPU	Mali-T764
Memory	2GB
Storage	
Warranty	3 years

IO-interface

Ethernet	10/100/1000 Gigabit BASE-T
WLAN	802.11 b/g/n
Bluetooth	Yes
USB	2 x USB2.0
ADB	1 x Micro USB for ADB
Analog Audio1 x 3.5mm stered	o output / Mic-in (combo jack)
Digital Audio	1 x SPDIF output
COM port	1 x RS-232 control port
Storage Expansion	1 x Micro SDHC slot

Mechanical and environment

Dimension (WxDxH)	. 165x118.5x27mm (6.49" x 4.66" x 1.06")
Mounting	. Easy wall mount/VESA mount 10x10 cm
Operating temperature	40°C to 70°C (-40°F to 158°F)
Storage temperature	40°C to 80°C (-40°F to 176°F)
Housing	durable Aluminum
Anti-theft lock compatible	eYes
Regulatory	CE/FCC/RoHS/BSMI
Power Adapter	DC12V, 1.5A

BXP-301 specific features

PiP		.1080p HDMI In
-----	--	----------------

*4k UHD Video not supported in portrait mode

BXP-300



BXP-301



